

COUPLING FOR PIPE CONNECTION AND PIPE REPAIR MECHANIZED SERIES

Configuration: 2 Closures



Repair coupling for pipe materials like steel.

MATERIALS

| | |
|----------------------|--|
| Casing: | Carbon steel. Epoxy coated |
| Reinforcement sheet: | Stainless steel AISI 304L or AISI 316L |
| Screws: | Carbon steel threaded rods |
| Gasket : | EPDM rubber in accordance with regulation UNE-EN-681-1. Compatible with potable water according ACS and WRAS and D.M. 174/2004 Also available in NBR and H-NBR |



SPECIFICATIONS

Available in diameters between 150 and 500 mm (all diameters covered), Nominal Pressure 25 / 40 / 100 bar

High anti corroding resistance due to epoxy coating.

No axial movements allowed. No angular deviation allowed.

For temperatures between -10° C /14 F and + 95° C /203 F

Pressures over 40 bar (depending on the diameter)

Test pressure = Working pressure x 1,5



DISTRIBUTED BY:



INSTALLATION AND SAFETY ADVICE

Apply the recommended torque during installation
Do not exceed or add up indicated parameters of tolerance
Use safety shoes and gloves during fitting and maintenance

Do not restrain axial pipe movements

All technical information reflected here is based on our experience, and on result of tests. Specifications are subject to change without previous advice. © 2018. Subject to technical modifications. For further information, please contact to our distributor.

